Rockford Sanitary Systems, Inc. ROCKFORD, IL 61125-0963

(815) 229-5077 - (800) 747-5077 - FAX (815) 229-5108 WEB SITE-www.rkfdseparators.com E MAIL-rssem@inwave.com

MODEL NO. GFE-1820-M GREASE SEPARATOR

DRAWN BY QUOTE # JOB NAME W.R.W. OPTIONAL FEATURES (ADDITIONAL COST) ☐ ANCHOR FLANGE ☐ CLAMP RING DUTLET RECESSED LIFT HANDLES IN COVERS **INLET** □ EPOXY COATING □ ANODES □REINFORCED COVER ⊐ALUMINUM C□VER STAINLESS STEEL CONSTRUCTION 8.50 ☐ SEDIMENT BASKET ☐ FILTER MEDIA INTEGRAL EXTENSION 12.00 INCHES □ALTERNATE VENT TAPPING SIZE ____ INCHES □ALTERNATE INLET & DUTLET SIZE____INCHES CAST IRON DUTLET FITTINGS □PVC DUTLET FITTINGS 28.50 17.00 23.00 14.50 17.50 29.50 15.00 12.00 DUTLET **INLET**

Specifications

Rockford Model GF-1820 all welded 10 Ga. steel separator, 17 gallon static capacity, 20 g.p.m. intermittent flow, 2.00" tapped inlet and outlet connection, 86 lbs. greasy sludge capacity, visible double-wall outside trap seal, easily removable filter screen removable 3/8" nonskid diamond tread-plate cover for flush in the floor installation suitable for pedestrian traffic secured with stainless flat head screws, heavy duty leak-proof gasket, OPEX Shop Coat coating inside and bituminous coating outside.

Optional features (Additional cost) listed above

Approved By Company Date